

Security Cable

Catalog #S214USOR

NEC/CEC: FPLR(ETL)

CABLE CONSTRUCTION:

CENTER CONDUCTOR:

14 AWG Solid Bare Copper

INSULATION:

PVC

Nom. Wall: 0.013"

Dia. over Insulation: 0.090"

Black and Red

SHIELD:

UnShielded

JACKET:

Red PVC

Dia. over Jacket: 0.212"

Nominal Jacket Thickness: 0.015"

Center Conductor

Insulation

FR Ripcord

Jacket



MECHANICAL SPECIFICATION

CABLE WEIGHT	36.00 #/MFT
MINIMUM BEND RADIUS	2.2"
OPERATION TEMPERATURE -20°C to 75°C	

ELECTRICAL PROPERTIES:

OPERATING VOLTAGE: 300 VRMS
 MAX CONDUCTOR DCR: 2.52 Ohms/MFT
 CAPACITANCE: 34.0 pF/Ft. Nom.
 FLAME TEST: FPLR NEC ART 760

FEATURES & BENEFITS:

Virgin materials
 Footage marking
 FPLP per NEC Article 760
 Pure copper conductors
 Custom colors, print, lengths available
 (minimum order quantities apply)

APPLICATIONS:

Commercial audio
 Security systems
 Power limited controls
 Sound & audio
 Intercom/PA systems
 Broadcast
 Nurse call